

# FU40

## 6 Position LED Standard Blade Fuse Box

• <b>Specifications:</b>	<ul style="list-style-type: none"><li>• suitable for use in automotive, leisure and marine applications</li><li>• red LED light indicating a fuse has blown</li><li>• an earth is not required when the fuse is blown as the fusebox will illuminate</li><li>• easy to identify blown fuses and makes for easy problem solving</li><li>• holds standard blade fuses only</li><li>• 4-hole fixing</li><li>• high quality clear cover (PC)</li><li>• Black base (PBT)</li><li>• White push button (POM)</li><li>• Tin plated copper terminal</li></ul>
• <b>Temperature range:</b>	-20°C to 85°C
• <b>Max. per box:</b>	100A (#10-32 threaded studs)
• <b>Max. per fuse/circuit:</b>	30A
• <b>Dimensions:</b>	W63mm x H35.5mm x L85mm ± 1mm
• <b>Voltage (Max):</b>	32 VDC
• <b>Connecton Pad Option Available:</b>	Input wire size: #4-6 AWG Output wire size: #12-16 AWG
• <b>Torque Rating:</b>	20 in-lb (2.25Nm) max.
• <b>Mounting Torque Rating:</b>	8 in-lb (0.9Nm) max.



The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. BEAL UK cannot be held responsible for product failure unless full testing has been carried out.