

# PCL Airline Gauge & Tyre Inflator

## AL12

- |                               |  |
|-------------------------------|--|
| • <b>Temperature range:</b>   | -10°C to 60°C  |
| • <b>Max. inlet pressure:</b> | 200 psi - 13.8 bar   |
| • <b>Main benefits:</b>       | <ul style="list-style-type: none"> <li>• Larger screen and clearer to read scale</li> <li>• New Valve Mechanism - Simplified 2 stage mechanism design prevents user having to "push" against full line pressure on deflate preventing fatigue</li> <li>• Biomorphic Shape - Ergonomic, easier to use and less prone to damage when dropped</li> <li>• Improved Piston &amp; Seal Design - New design, less drag, reduced friction &amp; less movement inertia means no internal corrosion, no sticking and no skewing of accuracy</li> <li>• Accuracy Standards - Tested to over 400,000 cycles at 100% accuracy</li> <li>• Accuracy compliant with BS EN 12645:2014</li> <li>• Display type: linear</li> <li>• Tye Valve Connection: Twin Hold-on</li> <li>• Calibration: 0-138 psi/0-9.6 bar</li> <li>• Flow rate: 500l/min @13 bar supply</li> <li>• Inlet/Outlet Connection: Rp 1/4</li> </ul> |



Item No.	Type	Display resolution	Hose Length(m/in)	Weight (kg)	Max. pressure
AL12	Tyre Inflator	2 psi / 0.1 bar	0.53/21	0.955	200 psi