


DATASHEE


Self Adhesive Cable C/Steel Clip

• Material:	Steel (ST)	ROHS
Adhesive:	Acrylate with base of polyethylene foam	COMPLIANT
Operating temperature:	-40°C to + 60°C	
• Features:	 Bendable metal tongue for any shape or configurations of wires or cables Cost effective with easy application on smooth, cleam surfaces. Perfect to apply when access is difficult. 	

• Great for domestic appliances and trailers.







Item No.	Colour	W (mm)	L (mm)	Bundle diameter max(mm)
SA1	White	20	30	4.0
SA2	White	25	36	8.0
SA3	White	31	44	12.0
SA4	White	38	54	16.0

IMPORTANT NOTE

1. The data above are typical values only, and should not be used for specifications purpose.

2. Tolerance: Thickness: ±10µm; finished product width ±1mm coil width ±2mm, length finished product ±0.3m coil ±0.5%

STORAGE & SHELF LIFE: 12 months when stored at 23±2°C (73°F) / 50% relative humidity out of direct sunlight.

SURFACE PREPARATION: It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application.

The quoted values are average and should not be taken as maximum or minimum values for specific purposes. BEAL UK Ltd cannot be held responsible for product failure unless full testing has been carried out.

The user has to decide on the tapes suitability for their own applications.