


# Semi Rigid Nylon Tubing

## Yellow (30 m)

• <b>Material:</b>	Quality grade nylon granules.
• <b>Temperature range:</b>	-40°C to +80°C
• <b>Function:</b>	Ideal for use in pneumatic control systems, chemical transfer and low-pressure hydraulic systems.
• <b>Features:</b>	<ul style="list-style-type: none"> <li>• UV stable.</li> <li>• Silicone free.</li> <li>• Abrasion resistant.</li> <li>• Working pressure 4 to 1 safety factor.</li> <li>• <b>Tube is not suitable for use with water or in high humidity environments.</b></li> </ul>



A = O.D. mm  
B = I.D. mm  
C = Wall Thickness mm

### Tolerances

4mm - 10mm OD  $\pm 0.1$ mm  
11mm - 18mm OD  $\pm 0.15$ mm  
 $\pm 0.5\%$  on weight

Item No.	A (mm)	B (mm)	C (mm)	Working pressure @23oC (bar)	Bend radius (mm)	Weight per 100m (kg)
TH44	4	2.5	0.75	38	60	0.88
TH45	5	3	1	42	60	1.42
TH46	6	4	1	33	90	1.71
TH47	8	6	1	24	130	2.50
TH48	10	8	1	19	160	3.19
TH49	12	9	1.5	24	200	5.69