

Helacon Plus Mini Connector

Push-in

• Materials:	Transparent Polycarbonate (PC)
• Operating Temperature:	-30°C to +85°C
• Flammability:	UL 94 V0
• Specifications:	2006/65/EC, ANSI/UL 486-A, ANSI/UL 486-B, ANSI/UL 486-C, cULus, DIN EN 60998-2-2:2005-03, EN 60998-2-2:2004, ENEC, NF EN 60695-2-10 (2013), NF EN 60695-2-11 (2014)
• UV Stabilised:	No
• Features:	<ul style="list-style-type: none"> • Fast reliable alternative to connector strip • 40 % smaller – Space saving design • Low insertion force – Easy to use, saves time on installation • Easy access to voltage test entry and innovative port shape design • Correct installation can be visually checked through transparent housing • Different colour codes for easy identification of size • Allows different conductor diameters in each entry • double spring which is approved for solid and stranded wires. • Safe application, installation and maintenance • Available in assorted box (150 pc)



Item No.	Colour	No. of conductors	Solid Wire Range (mm ²)	Stranded Wire Range (mm ²)
HCPM2	Yellow	2	0.5-2.5	0.5-1.5
HCPM3	Orange	3	0.5-2.5	0.5-1.5
HCPM4	Clear	4	0.5-2.5	0.5-1.5
HCPM5	Blue	5	0.5-2.5	0.5-1.5
HCPM6	Violet	6	0.5-2.5	0.5-1.5
HCPM8	Black	8	0.5-2.5	0.5-1.5
AT169	Assorted	2-8	0.5-2.5	0.5-1.5